Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015 Issue date: 2024-07-04 Revision date: 2024-07-04 Version: 1.0

SECTION 1: Identification	
1.1. Identification	
Product form Product name Product code	 Mixture Artemis 2 Acrylic Coating SGA2
1.2. Recommended use and restrictions of	on use
Use of the substance/mixture Restrictions on use	Roof restoration and repairIndustrial use
1.3. Supplier	
Supplier SkyGuard Coatings LLC 1225 Brai Drive Port Arthur, TX 77640 - USA T 409-344-1040 skyguardcoatings.com	
1.4. Emergency telephone number	
Emergency number	: CHEMTREC 1-800-424-9300
SECTION 2: Hazard(s) identification 2.1. Classification of the substance or mi GHS classification Skin Sens. 1	xture
2.2. GHS Label elements, including preca	uutionary statements
GHS labelling Hazard pictograms (GHS)	
Signal word (GHS) Hazard statements (GHS) Precautionary statements (GHS)	 Warning May cause an allergic skin reaction. Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Calcium carbonate	Calcium carbonate C.I. Pigment White 18 / Calcium carbonate / Pigment White 18 / C.I. 77220 / Carbonic acid, calcium salt / CALCIUM CARBONATE / CI 77220 / calcium carbonate	CAS-No.: 471-34-1	10 - 30
Cellulose, 2-hydroxyethyl ether	Cellulose, 2-hydroxyethyl ether Hydroxyethyl cellulose / Hydroxyethylcellulose / 2- Hydroxyethyl cellulose / HYDROXYETHYLCELLULOSE / Cellosize hydroxyethyl cellulose / Ethyl cellulose resin / Cellulose, hydroxyethyl ether	CAS-No.: 9004-62-0	0.5 - 1.5
Titanium Dioxide	Titanium Dioxide C.I. 77891 / C.I. Pigment White 6 / Titanium oxide (TiO2) / CI 77891 / Titanium(IV) oxide / C.I. Pigment White 7 / Pigment White 6 / Titanium oxide	CAS-No.: 13463-67-7	0.5 - 1.5
1,2-Benzisothiazol-3(2H)-one	1,2-Benzisothiazol-3(2H)-one BENZISOTHIAZOLINONE / Benzisothiazolin-3-one, 1,2- / 1,2-Benzisothiazol-3-one / 1,2-Benzisothiazolone / Benzisothiazolinone / 1,2-Benzisothiazolin-3-one / benzisothiazolinone	CAS-No.: 2634-33-5	<0.1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.
4.2. Most important symptoms and effe	cts (acute and delayed)
Symptoms/effects after inhalation Symptoms/effects after skin contact	 May cause irritation to the respiratory tract. May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Symptoms/effects after ingestion

: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures		
5.1. Suitable (and unsuitable) exting	uishing media	
Suitable extinguishing media Unsuitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.: Do not use water jet.	
5.2. Specific hazards arising from the chemical		
Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon. Calcium oxide.	
5.3. Special protective equipment and precautions for fire-fighters		
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).	

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipm	ent and emergency procedures	
General measures	Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.	
6.1.1. For non-emergency personnel		
No additional information available		
6.1.2. For emergency responders		
No additional information available		
6.2. Environmental precautions		
Prevent entry to sewers and public waters.		
6.3. Methods and material for containment an	nd cleaning up	
	Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.	
Methods for cleaning up	Sweep or shovel spills into appropriate container for disposal. Provide ventilation.	

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.
Hygiene measures	: Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Always wash hands after handling the product.

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool and wellventilated place.

SECTION 8: Exposure controls/personal protection 8.1. Control parameters **Artemis 2 Acrylic Coating** No additional information available Calcium carbonate (471-34-1) **USA - NIOSH - Occupational Exposure Limits** NIOSH REL TWA 10 mg/m³ (total dust) 5 mg/m³ (respirable dust) Cellulose, 2-hydroxyethyl ether (9004-62-0) No additional information available Titanium Dioxide (13463-67-7) **USA - ACGIH - Occupational Exposure Limits** Local name Titanium dioxide ACGIH OEL TWA 0.2 mg/m³ (nanoscale respirable particulate matter) 2.5 mg/m³ (finescale respirable particulate matter) TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen) Remark (ACGIH) Confirmed Animal Carcinogen with Unknown Relevance to Humans ACGIH chemical category Regulatory reference ACGIH 2020 **USA - OSHA - Occupational Exposure Limits** Local name Titanium dioxide (Total dust) OSHA PEL TWA 15 mg/m³ (total dust) Regulatory reference (US-OSHA) **OSHA** Annotated Table Z-1 **USA - IDLH - Occupational Exposure Limits** IDI H 5000 mg/m³ **USA - NIOSH - Occupational Exposure Limits** NIOSH REL TWA 2.4 mg/m3 (CIB 63-fine) 0.3 mg/m³ (CIB 63-ultrafine, including engineered nanoscale) 1,2-Benzisothiazol-3(2H)-one (2634-33-5) No additional information available 8.2. Appropriate engineering controls Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eve wash stations and safetv showers. : Avoid release to the environment. Environmental exposure controls

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and c	hemical properties	
Physical state	: Liquid	
Appearance	No data available	
Colour	: No data available	
Odour	: No data available	
Odour threshold	: No data available	
pH	: 10	
Melting point	: No data available	
Freezing point	: No data available	
Boiling point	: 212 °F (100 °C)	
Flash point	: >212 °F (>100 °C)	
Relative evaporation rate (butylacetate=1)	: No data available	
Flammability	: Not flammable.	
Vapour pressure	: No data available	
Relative vapour density at 20°C / 68 °F	: No data available	
Relative density	: No data available	
Solubility	: No data available	
Partition coefficient n-octanol/water	: No data available	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
Viscosity, kinematic	: 15000 mm²/s @ 104 °F (40 °C)	
Viscosity, dynamic	: No data available	
Explosive limits	: No data available	

: No data available

- No data available :
 - : No data available

9.2. Other information

Explosive properties

Oxidising properties

No additional information available

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 10: Stability and reac	livity	
10.1. Reactivity		
No dangerous reactions known under nor	nal conditions of use.	
10.2. Chemical stability		
Stable under normal conditions.		
10.3. Possibility of hazardous reac	lions	
No dangerous reactions known under nor	nal conditions of use.	
10.4. Conditions to avoid		
Heat. Incompatible materials.		
10.5. Incompatible materials		
Strong oxidizers. Strong acids.		
10.6. Hazardous decomposition pr	oducts	
May include, and are not limited to: oxides	of carbon. Calcium oxide.	
SECTION 11: Toxicological info	rmation	
11.1. Information on toxicological e	ffects	
Acute toxicity (oral) Acute toxicity (dermal)	: Not classified. : Not classified.	

	Not plassified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.
Calcium carbonate (471-34-1)	
LD50 oral rat	6450 mg/kg (Source: NLM_CIP)
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
LC50 inhalation rat	 > 3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
ATE CA (oral)	6450 mg/kg bodyweight
Titanium Dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LC50 inhalation rat	5.09 mg/l/4h
ATE CA (vapours)	5.09 mg/l/4h
ATE CA (dust,mist)	5.09 mg/l/4h
1,2-Benzisothiazol-3(2H)-one (2634-33-5)	
LD50 oral rat	1020 mg/kg (Source: NZ_CCID)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
ATE CA (oral)	1020 mg/kg bodyweight

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

5	,
Skin corrosion/irritation	: Not classified.
	pH: 10
Serious eye damage/irritation	Not classified.
	pH: 10
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified.
1,2-Benzisothiazol-3(2H)-one (2634-33-5)	
NOAEL (animal/female, F0/P)	112 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800
	(Reproduction and Fertility Effects)
NOAEL (animal/female, F1)	56.6 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800
	(Reproduction and Fertility Effects)
STOT-single exposure	: Not classified.
Cellulose, 2-hydroxyethyl ether (9004-62-0)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified.
Calcium carbonate (471-34-1)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated
	Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	≥ 0.212 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity:
	90-Day Study)
Aspiration hazard	: Not classified.
Artemis 2 Acrylic Coating	
Viscosity, kinematic	150000 mm²/s @ 104 °F (40 °C)
Or man ta sea da ffa a ta la fila se la tila da	Name and a further than to the annual term to at
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after inhalation Symptoms/effects after skin contact	 May cause irritation to the respiratory tract. May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.
Symptoms/effects after skin contact	 May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction. May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear
Symptoms/effects after skin contact	 May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction. May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after skin contact	 May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction. May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and
Symptoms/effects after skin contact	 May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction. May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general :	May cause long-term adverse effects in the aquatic environment.
Titanium Dioxide (13463-67-7)	
LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19.3 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 - Crustacea [2]	27.8 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

1,2-Benzisothiazol-3(2H)-one (2634-33-5)	
LC50 - Fish [1]	≈ 16.7 mg/l Test organisms (species): Cyprinodon variegatus
EC50 - Crustacea [1]	2.94 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	2.15 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [2]	2.9 mg/l Test organisms (species): Daphnia magna

12.2. Persistence and degradability

Artemis 2 Acrylic Coating		
Persistence and degradability	Not established.	
12.3. Bioaccumulative potential		
Artemis 2 Acrylic Coating		
Bioaccumulative potential	Not established.	
Calcium carbonate (471-34-1)		
BCF - Fish [1] (no bioaccumulation)		
1,2-Benzisothiazol-3(2H)-one (2634-33-5)		
Partition coefficient n-octanol/water	0.99 (at 20 °C (at pH 5)	
12.4. Mobility in soil		

No additional information available

12.5. Other adverse effects	
Other information	: No other effects known.

SECTION 13: Disposal considerations	
13.1. Disposal methods	
Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

SECTION 14: Transport information	
In accordance with DOT / TDG	
14.1. UN number	
UN-No.(DOT) UN-No. (TDG)	Not applicableNot applicable
14.2. UN proper shipping name	
Proper Shipping Name (DOT) Proper Shipping Name (TDG)	Not applicableNot applicable
14.3. Transport hazard class(es)	
DOT Transport hazard class(es) (DOT)	: Not applicable

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

TDG

Transport hazard class(es) (TDG)	: Not applicable
14.4. Packing group	
Packing group (DOT) Packing group (TDG)	: Not applicable : Not applicable
14.5. Environmental hazards	
Other information	: No supplementary information available.
14.6. Special precautions for user	
Special transport precautions	: Do not handle until all safety precautions have been read and understood.
14.7. Transport in bulk according to Annex	II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:	
Silica, amorphous, precipitated and gel	CAS-No. 112926-00-8
Silica, amorphous, fumed, crystalline-free	CAS-No. 112945-52-5

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		
2-Propenoic acid	CAS-No. 79-10-7	0.0001 – 0.001%
Isopropyl alcohol	CAS-No. 67-63-0	< 1%
Diethanolamine	CAS-No. 111-42-2	< 1%

Ammonium hydroxide (1336-21-6)	
CERCLA RQ	1000 lb

2-Propenoic acid (79-10-7)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	5000 lb

Diethanolamine (111-42-2)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	100 lb

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

15.2. International regulations

No additional information available

15.3. US State regulations

This product can expose you to Diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Titanium Dioxide(13463-67-7)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List
oxydipropanol(25265-71-8)	U.S Pennsylvania - RTK (Right to Know) List
1,2-Propanediol(57-55-6)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Ammonium hydroxide(1336-21-6)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Carbonic acid, magnesium salt (1:1)(546-93-0)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Massachusetts - Right To Know List
2-Propenoic acid(79-10-7)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Silica, amorphous, precipitated and gel(112926-00-8)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List
Ethanedial(107-22-2)	U.S New Jersey - Right to Know Hazardous Substance List
Limestone(1317-65-3)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List
Isopropyl alcohol(67-63-0)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Diethanolamine(111-42-2)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015 Revision date : 07/04/2024 Other information : None.

Full text of hazard	I classes and H-statements
Skin Sens. 1	Skin sensitisation, Category 1

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.